

LUCY

SALINITY RESISTANT



LUCY



LUCY

SALINITY RESISTANT



LUCY

SALINITY RESISTANT

The carefully chosen materials and the high corrosion protection make this product suitable for installation in saline environments.

The versions with external body in Stainless Steel and external body in Nylon are resistant to corrosion and recyclable, remaining unaltered even in the face of high temperatures and aggressive atmospheric agents.

The absence of iron components, which oxidizing degrades the steel, determines a high longevity of the appliance in unfavorable environmental conditions such as coastal areas with high salinity.

LINKED PRODUCTS



LUCY WALL RECESSED
Pag. 210



LUCY GROUND RECESSED
Pag. 256



Always consult www.augentighting.it for
UPDATED TECHNICAL DATA



WALL
LUCY

1050
Stainless Steel



1051
Aluminium



1052
Nylon

APPLICATION



Versatile luminaire available in recessed wall, floor recessed and wall mounted versions. The recessed wall and floor recesses have reduced depth and an AISI316L stainless steel ring which guarantee a very high resistance to oxidation. Also available with an octagonal-shaped ring that allows interesting architectural combinations. The Lucy model wall lamp is available in NYLON, painted aluminum or AISI316L stainless steel.

CHARACTERISTICS

- Optical system housing accessible during installation.
- Wall connection system with plastic anchoring plate
- Connection to the power supply network through cable gland for cables with a maximum diameter of 11mm type H07RN-F 3x1.5 or similar.
- LED maintenance by opening the optical compartment.
- Fixed output system with SMD LEDs with direct power supply 220-240Vac.
- Luminaire Conforms to EN60598-1 Standard and special requirements

MATERIALS

- Ring AISI316L Steel (1050W) / Aluminum Alloy (1051W) / Polyamide PA6 (1052W).
- Wall fixing plate in Polyamide (PA6) filled with 30% GWT960 UV Resist.
- Diffuser in extra-clear acid-etched glass internally LTF > 60%.
- Seals in EDPM closed cell rubber, UV- resist. Tx -40/+150°C.
- Passive heatsink in aluminum alloy for extrusion.
- Internal and external screws in A2 Stainless Steel
- Polyester powder coating, UV-stabilised with anti-corrosion treatment.

WALL

LUCY

SPECIFICATIONS



Installation:
Wall/Ceiling

- The rated flux values refer to source LED at Ts70°C / ta25°C
- The Power/Flux in the table refer to maximum installable value
- Code 1050 - Stainless Steel Body AISI316L
- Code 1051 - Aluminium Body



1050W - STAINLESS STEEL BODY





99
STAINLESS STEEL AISI316L


LED DIRECT AC SYSTEM

SALINITY RESISTANT

| COD. | Source Flux | Fixture Flux | CCT | CRI | Power | CL |
|-----------------|-------------|--------------|--------|-----|-------------------------|----|
| 1050W/WR1.VS.99 | 450 lm | 260 lm | 3000 K | 80 | 5W - 220-240Vac 50/60Hz | II |
| 1050W/NR1.VS.99 | 475 lm | 275 lm | 4000 K | 80 | 5W - 220-240Vac 50/60Hz | II |





DIMENSIONS




LED DIRECT AC SYSTEM

| COD. | Source Flux | Fixture Flux | CCT | CRI | Power | CL |
|--------------|-------------|--------------|--------|-----|-------------------------|----|
| 1051W/WR1.VS | 450 lm | 260 lm | 3000 K | 80 | 5W - 220-240Vac 50/60Hz | II |
| 1051W/NR1.VS | 475 lm | 275 lm | 4000 K | 80 | 5W - 220-240Vac 50/60Hz | II |



ASSEMBLY



COLOUR 1052W - NYLON BODY




30
ANTHRACITE

LED DIRECT AC SYSTEM

SALINITY RESISTANT

| COD. | Source Flux | Fixture Flux | CCT | CRI | Power | CL |
|--------------|-------------|--------------|--------|-----|-------------------------|----|
| 1052W/WR1.VS | 450 lm | 260 lm | 3000 K | 80 | 5W - 220-240Vac 50/60Hz | II |
| 1052W/NR1.VS | 475 lm | 275 lm | 4000 K | 80 | 5W - 220-240Vac 50/60Hz | II |



STANDARD COLOURS 1051W

