

WALL

UP&DOWN



APPLICATION



Wall-mounted luminaires configurable in single and double emission, ideal for grazing lighting of external facades. Up & Downd is equipped with various secondary optics for controlling the luminous flux, which allow design flexibility through different combinations of direct and indirect emission. The fixture includes the use of LED sources with built-in driver with fixed output or Dali dimmable on request with extra charge.

WALL

UP&DOWN MINI

SPECIFICATIONS



- The rated flux values refer to source LED at Ts80°C / ta25°C
- The Power/Flux in the table refer to maximum installable value
- Lower powers are available on request, only for version with built-in driver
- Single Emission version can be oriented both upwards and downwards



LED SYSTEM WITH BUILT-IN DRIVER - Single Emission

REVIEW


COD.	Source Flux	Fixture Flux	CCT	CRI	Power	CL
7551W/WC0.XX	793 lm	723 lm	3000 K	80	8W - 220-240Vac 50/60Hz	I
7551W/NC0.XX	825 lm	752 lm	4000 K	80	8W - 220-240Vac 50/60Hz	I

Beam XX :
 XX=NB (Flood 10°)
 XX=MB (Flood 26°)
 XX=WB (Wide Flood 56°)

Single Emission
 Clear Glass

Not dimmable

DIMENSIONS



LED SYSTEM WITH BUILT-IN DRIVER - Double Emission

REVIEW

COD.	Source Flux	Fixture Flux	CCT	CRI	Power	CL
7550W/WC0.XX	1586 lm	1446 lm	3000 K	80	16W - 220-240Vac 50/60Hz	I
7550W/NC0.XX	1650 lm	1504 lm	4000 K	80	16W - 220-240Vac 50/60Hz	I

Beam XX :
 XX=NB (Flood 10°+10°)
 XX=MB (Flood 26°+26°)
 XX=WB (Wide Flood 56°+56°)
 XX=NW (Double Flood 10°+56°)

Double Emission
 Clear Glass

Not dimmable

STANDARD COLOURS



UP&DOWN


SPECIFICATIONS



- The rated flux values refer to source LED at Ts80°C / ta25°C
- The Power/Flux in the table refer to maximum installable value
- Lower powers are available on request, only for version with built-in driver
- Dimmable system available on request only with built-in driver
- Single Emission version can be oriented both upwards and downwards



DIMENSIONS



LED SYSTEM WITH BUILT-IN DRIVER - Single Emission

REVIEW

COD.	Source Flux	Fixture Flux	CCT	CRI	Power	CL
7501W/WC3.XX	1927 lm	1523 lm	3000 K	80	17W - 220-240Vac 50/60Hz	I
7501W/NC3.XX	2003 lm	1583 lm	4000 K	80	17W - 220-240Vac 50/60Hz	I

Beam XX :
 XX=NB (Flood 16°)
 XX=MB (Flood 29°)
 XX=WB (Wide Flood 48°)

Single Emission
 Clear Glass

Dali dimmable on request
 with extra charge

LED SYSTEM WITH BUILT-IN DRIVER - Double Emission

REVIEW

COD.	Source Flux	Fixture Flux	CCT	CRI	Power	CL
7500W/WC3.XX	3854 lm	3046 lm	3000 K	80	33W - 220-240Vac 50/60Hz	I
7500W/NC3.XX	4006 lm	3166 lm	4000 K	80	33W - 220-240Vac 50/60Hz	I

Beam XX :
 XX=NB (Flood 16°+16°)
 XX=MB (Flood 29°+29°)
 XX=WB (Wide Flood 48°+48°)
 XX=NW (Double Flood 16°+48°)

Double Emission
 Clear Glass

Dali dimmable on request
 with extra charge

STANDARD COLOURS

